



**Reliable infrared open path  
gas detection for ducts**

# Cross-Duct Technology



## Applications include

- Control rooms
- Personal refuge areas
- Turbine enclosures

## Features & benefits

- Fast speed of response provides earliest warning
- High sensitivity allows low alarm set points
- Alignment free design makes installation simple
- Duct flex and vibration tolerance keeps the system online
- Integral functional gas test facility allows for simple system check
- Contamination resistant optics reduce the need for unscheduled maintenance
- Immune to catalytic poisons
- Works in inert atmospheres

## Based on the proven open path design, Searchline Excel Cross-Duct was developed in response to the unique requirements for monitoring in HVAC ducting and Turbine Enclosures.

Searchline Excel Cross-Duct delivers the highest speed of response at low alarm set points over a wide temperature range

With continuous improvement and the highest quality manufacturing and control processes, Honeywell Analytics Searchline Excel Open Path flammable gas detector provides best in class gas detection. Searchline Excel is often the chosen primary flammable gas detector in conjunction with Searchpoint Optima Plus as complimenting flammable point detection.

Cross duct flammable gas detectors compliment other system gas protectors such as toxic gas detection, providing a fast and effective protection to gas ingress into ventilation ducts.



## Modbus digital output - know before you go!

Searchline Excel is also available as a kit with the XNX Universal Transmitter, featuring both a local HART® port and HART® over 4 to 20mA as standard. These solutions allow configuration of the Searchline Excel through the XNX user interface or using a compatible HART® hand-held interrogator one device. Alternatively, an intrusive

connection to the Searchline Excel using an SHC-1 hand-held interrogator together with an SHC-1 protection device module can be made in applications that allow such operations.

The multi drop Modbus capability can enable significant savings in installation and cabling costs. A single comms cable can be run between up to 32 detectors instead of the

usual 'single run' required for each detector. Additionally, the 2 way digital communication protocol allows configuration, warning and fault diagnosis information to be communicated back to the control room. This reduces servicing and maintenance costs as the operator can diagnose the state of any individual unit before deciding to send anyone into the field.



# Technical Summary

## Searchline Excel Cross-Duct



Specification	
Available Gas Calibrations	Methane (gas mixtures where methane is the main constituent (>70%) and the balance is C <sub>2</sub> - C <sub>6</sub> hydrocarbons)*
Detection Range	0-100% LEL
Minimum Alarm Thresholds	20% LEL (>0.5 to 2.5m duct width) 10% LEL (>2.5m to 5m duct width)
Speed of Response	T90 < 1 second
Output Signals	Measuring range: 4-20mA sink or source (Default current source) Over range: 21mA Warning: 3mA Beam Block: 2.5mA Inhibit: 2mA Fault: 0mA
Diagnostics	RS485 serial link
Digital Output	Modbus RS485 multi drop. (Using DX100(M) or XNX Universal Transmitter with Modbus option)
Operating Temperature	-40°C to +50°C (-40°F to 122°F) ambient. An internal duct temperature of up to 60°C (140°F) is acceptable, provided the ambient temperature outside the duct at the Transmitter and Receiver unit is within the operating range. Contact Honeywell Analytics for high temperature applications
Operating Humidity	0-99% (non condensing)
Operating Pressure	91.5-105.5 kPa (non compensated)
Repeatability	5.0% LEL (<1 metre duct width) 2.5% LEL (>1 metre duct width)
Warm-up Time	<1 hour (fully stabilised)
Power Supply	Unit: 18 to 32V dc Heated Reflector Panel: 18 to 28V dc
Power Consumption	Unit: 13W max. Heated Reflector Panel: 6W (nom) @ 24VDC
Enclosure Material	316 Stainless steel
IP Rating	IP66 and IP67
Weight	Transceiver 13kg, reflector panel 5kg (>0.5m to 2.5m duct width), 10kg (>2.5 to 5.0m duct width)
Vibration	2-60Hz, max ptp amplitude 1mm
EMC Standards	EN50270
Safety Approvals	<div><b>ATEX</b> Transmitter: II 2 G Ex d op is IIC T5 (T<sub>amb</sub> -40°C to +65°C) Gb II 2 G Ex d op is IIC T6 (T<sub>amb</sub> -40°C to +40°C) Gb  Receiver: II 2 G Ex d IIC T5 (T<sub>amb</sub> -40°C to +65°C) Gb II 2 G Ex d IIC T6 (T<sub>amb</sub> -40°C to +40°C) Gb  <b>Heated Panel</b> ATEX: II 2 G Ex d IIC Gb T3 (T<sub>amb</sub> -40°C to +60°C) UL: Class 1, DIV 1, Groups B, C, D T<sub>amb</sub> -40°C to +60°C</div> <div><b>IECEx</b> Transmitter: Ex d op is IIC T5 (T<sub>amb</sub> =-40°C to +65°C) Gb Ex d op is IIC T6 (T<sub>amb</sub> =-40°C to +40°C) Gb  Receiver: Ex d IIC T5 (T<sub>amb</sub> -40°C to +65°C) Gb Ex d IIC T6 (T<sub>amb</sub> -40°C to +40°C) Gb UL: Class 1 Groups B, C, D and Class 1 Zone 1 AEx d IIB + Hydrogen (Amb -40°C to +65°C)</div>

\*Contact Honeywell Analytics for other gases and approvals



# Honeywell Analytics Gas Detection



Honeywell Analytics is able to provide gas detection solutions to meet the requirements of all applications and industries. Contact us in the following ways:

## Headquarters

### Europe, Middle East, Africa

Life Safety Distribution AG  
Javastrasse 2  
8604 Hegnau  
Switzerland  
Tel: +41 (0)44 943 4300  
Fax: +41 (0)44 943 4398  
gasdetection@honeywell.com

#### Customer Service:

Tel: +800 333 222 44 (Freephone number)  
Tel: +41 44 943 4380 (Alternative number)  
Fax: +800 333 222 55  
Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)  
Middle East Tel: +971 4 450 5852 (Portable Gas Detection)

### Americas

Honeywell Analytics Distribution Inc.  
405 Barclay Blvd.  
Lincolnshire, IL 60069  
USA  
Tel: +1 847 955 8200  
Toll free: +1 800 538 0363  
Fax: +1 847 955 8210  
detectgas@honeywell.com

### Asia Pacific

Honeywell Analytics  
Asia Pacific  
#701 Kolon Science Valley (1)  
43 Digital-Ro 34-Gil, Guro-Gu  
Seoul 152-729  
Korea  
Tel: +82 (0) 2 6909 0300  
Fax: +82 (0) 2 2025 0388  
India Tel: +91 124 4752700  
analytics.ap@honeywell.com

## Technical Support Centres

Honeywell Analytics Ltd.  
4 Stinsford Road  
Nuffield Industrial Estate  
Poole, Dorset, BH17 0RZ  
United Kingdom  
Tel: +44 (0) 1202 645 544  
Fax: +44 (0) 1202 645 555

Honeywell Analytics  
ZAC Athélia 4 - 375 avenue du Mistral  
Bât B, Espace Mistral  
13600 La Ciotat  
France  
Tel: +33 (0) 4 42 98 17 75  
Fax: +33 (0) 4 42 71 97 05

Honeywell Analytics  
Elsenheimerstrasse 43  
80687 München  
Germany  
Tel: +49 89 791 92 20  
Fax: +49 89 791 92 43

Honeywell Analytics  
P.O. Box-45595  
6th Street  
Musaffah Industrial Area  
Abu Dhabi  
UAE  
Tel: +971 2 554 6672  
Fax: +971 2 554 6672

EMEA: HAexpert@honeywell.com  
US: ha.us.service@honeywell.com  
AP: ha.ap.service@honeywell.com

[www.honeywellanalytics.com](http://www.honeywellanalytics.com)  
[www.raesystems.com](http://www.raesystems.com)

**Honeywell Analytics**  
Experts in Gas Detection



#### Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

13463\_H\_Searchline Excel Cross Duct\_DS01153\_V1\_EMEA

02/15

© 2015 Honeywell Analytics

**Honeywell**



# DSA Suppliers

Thank you for reading this. For pricing or further information, please contact us.

W: <https://dsasuppliers.com>

E: [sales@dsasuppliers.com](mailto:sales@dsasuppliers.com)

P: +441158390391

---

Leading UK Supplier  
**Brand New & Genuine OEM Parts**  
Delivered Worldwide

---



Worldwide Delivery



1000+ Genuine Parts & Equipment

Please Note - The information, product designs & specifications in this document are subject to change without notice.  
DSA Suppliers is not responsible for determining the suitability of this product.